

XERO
TECHNOLOGY
ADVANCED 

XTA | 2.0 Edge Square IP55



metric

60mm Wide x 77mm High


imperial

2.362" Wide x 3.0315" High



XTA | 2.0 EDGE Square IP55

Highly Configurable



bend options


Note: IP series have non lit bends



135°




cross 90°



tee 90°



custom



corner 90°



ceiling to wall

DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500	
	Xeramix	CRI	80+		
		Lumen Maintenance:	114,000 Hours (L90 B10 @ 50°)		
	Proformax	CRI:	90+		
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)		
Warranty	Xeramix		10 years		
	Proformax		7 years		
Electrical	Power Consumption		Between 20 and 45w/m		
	Voltage input range		120 – 277V		
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI		
	Total harmonic distortion THD		9.8% max		
	Approvals		UL / CE / CCC / AS:NZS / EMC		
Physical	Dimensions		60 X 77 mm		
	Weight per metre		3kg (6.6lbs) average weight		
	Housing		Aluminium Extrusion with anodised or powder-coated finish		
	Diffuser		frosted acrylic lens / Polycarbonate lens / microprism lens		
	Connections		Gasketed section joints (non-continuous ribbon of light)		
	Compatible ceiling type		suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings		
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount		
	Joiner options		(Unlit Bends) corner 90°/ Cross 90°/ Tee 90°/ straight 180° Join		
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)		
	Environment		IP55 (Not in direct sunlight)		
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm		
	LED Board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible		

PENDANT LENGTHS

DESCRIPTION	PENDANT LENGTHS										
luminaire length	585	865	1145	1425	1705	1985	2265	2545	2825	3105	3385
inches	23	34	45	56	67	78	89	100	111	122	133
'560 board multiples	1	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0

CONTINUOUS LENGTHS

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	3665	3945	4225	4505	4785	5065	5345	5625	5905	6185	6465
inches	144	155	166	177	188	199	210	232	232	243	254
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	6745	7025	7305	7585	7865	8145	8245	8705	8985	9625	9545
inches	144	155	166	177	188	199	210	232	232	243	254
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

Above lengths are for Non-IP rated systems only. Lengths vary slightly when IP rated systems are selected please consult your local Xero Representative for more details

CUSTOM LENGTHS

CUSTOM LENGTHS
Custom lengths for Xeramix are available in 0.0393701" [1mm] increments above the minimum pendant length of 23" [590mm]
Custom lengths for Proformax are available in 0.984252" [25mm] increments above the minimum pendant length of 23" [590mm]

XTA | 2.0 EDGE Square IP55

Optical control

All XTA profiles come with many diffuser options for glare control in any application



polycarbonate




plexiglass




microprism


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights

XTA | 2.0 EDGE Square IP55



The Xero Configurator allows you to design and build your customised lighting system. To ensure that your profile specifically caters to your project application follow the simple 8 step build process to obtain your unique DNA code. Select your profile, choose your colour, length, gear tray, output, colour temperature, mounting requirement and choose from the selection of extras

XERO
Linear Lighting Systems


XTA 3.0 Beam


Name: Joe Smith
 Company: Joe Smiths Company
 Email: joesmith@joesmithcompany.com.au

Project: A very big project

Fitting Type:

Series	XTA - Advanced
IP Rating	IP55
LED Board	Xeramix X1
Size	3.0 Inches Down / 1.5 Inches Up
Shape	Beam
Light Output	Up / Down
Diffuser	Plexiglass Down / Parabolic Louver Up
Colour Temp	3000K Down / 5000K Up
Drive Current	Drive Current Down / Drive Current Up
Total Light	Total Light Down / Total Light Up
Total Power	Total Power Down / Total Power Up
Efficiency	Efficiency Down / Total Power Up











Copy and Paste into your project specification


SPECIFICATION TEXT
 Copy and Paste into your project specification

Type xx - XXM Xero XTA | 3.0 Square with Micro Prism diffuser, Xeramix I LED light engine, 3000°K, 50°C ambient temperature, L90 B10 114 hour life, 275Ma drive current. Efficacy of 512 lumens per watt delivered. Fitting comes complete with Speed-Connect joining system, Con Seal end plates and Lumiseal. Wire suspended with rollerball suspension system.

RE - CONFIGURE THIS SPECIFICATION

This project specification sheet has been generated with X Configurator. Click below to reconfigure and generate a new specification sheet.


[Click to re-configure](#)

ADELAIDE | AUCKLAND | BRISBANE | CHRISTCHURCH | DUNEDIN | HONG KONG
 KUALA LUMPUR | SYDNEY | MELBOURNE | PERTH | USA | WELLINGTON

XEROLIGHTING.COM

to access the X-configurator please visit www.xerolighting.com/xconfigurator

General enquiries
E headoffice@xerolighting.com W
xerolighting.com To get in touch with your local
Xero Distributor Visit [XEROContacts](#)



The information contained within this specification sheet is for general information purposes only. While Xero aspires to keep the information up to date and correct, we make no representations or warranties of any kind about the accuracy, reliability, suitability or availability with respect to this information, products, services, or graphics contained in this specification sheet for any purpose.