




XTA | 2.5 Orbit Beam 33.85" Run Length 106.37"

XTA | 2.5 Orbit Beam 65.35" Run Length 205.31"

XTA | 2.5 Orbit Beam 96.85" Run Length 304.25"







DATA TABLE

| Optic Module LED Engine | Proformax | CRI | 90+ |
|----------------------------|-----------|---|--------------|
| | | Lumen Maintenance | 82,000 Hours |
| Warranty | | 7 years | |
| Dimensions | | (Profile size 2.79" x 3.93) Orbit sizes - 33.85" x 33.85" / 65.35" x 65.35" / 96.85" x 96.85" | |
| Weight | | XTA 2.5 Orbit Slot 33.85" 23.8lbs / XTA 2.5 Ellipse Slot 65.35" 46.2lbs / XTA 2.5 Orbit Slot 96.85" 67.9lbs | |
| IP Rating | | IP20 (dry indoor application only) | |
| Compatible ceiling type | | Suitable for (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings | |
| Mounting | | Wire suspensions, rod suspensions, surface mounting, ceiling mounting | |

To create fully customisable variations of these profiles go to -

https://xerolighting.com/products/xta-2-5-loop-slot/

Genreral Enquiries: E headoffice@xerolighting.com W xerolightingusa.com | To get in touch with your local Xero Distributor visit xerolightingusa.com/contact

