




XTS | 2.0 Beam (Up / Down)



metric | 60mm Wide x 120mm High
imperial | 2.36" Wide x 4.72" High

*Illustration shows 'optional' screwless endplate



Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com



XTS | 2.0 Beam

DATA TABLE

	4 Ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500
LED Engine	Proformax	CRI:	90+	
		Lumen Maintenance:	82,000 Hours (L80 B10 @ 35°)	
Warranty	Proformax		7 years	
Electrical	Power Consumption		Between 20 and 45w/m	
	Voltage input range		120 - 277V	
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Diming control DMX or DALI XI	
	Total harmonic distortion THD		9.8% max	
	Approvals		UL / CE / CCC / AS:NZS / EMC	
Physical	Dimensions		60 x 120mm	
	Weight per metre		3.6kg (7.93lbs) average weight	
	Housing		Aluminium Extrusion with anodised or powder-coated finish	
	End Plates		Screwed End Plates (Standard) / Screw-Less End Plates (Optional)	
	Connections		Polarised electrical connection between sections	
	Downward diffuser		Frosted acrylic lens	
	Upward diffuser		Frosted acrylic lens	
	Compatible ceiling type		Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings	
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting /	
	Joiner options		Lit corner 90° / Cross 90° / Tee 90° / Straight 180° join	
	Operating temperatures		Proformax = -25°C to 35°C (-13°F to 95°F)	
	Environment		Dry indoor applications only	
	Minimum length adjustment		Proformax = 50mm	
	LED Board types		Proformax LED boards in 50 / 280mm / 560mm lengths	



Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com



XTS | 2.0 Beam

PENDANT LENGTHS

DESCRIPTION	PENDANT LENGTHS										
	572	852	1132	1412	1692	1972	2252	2532	2812	3092	3372
luminaire length											
inches	23	34	45	56	67	78	89	100	111	122	133
'560 board multiples	1	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0

CONTINUOUS LENGTHS

DESCRIPTION	CONTINUOUS RUNS										
	3652	3932	4212	4492	4772	5052	5332	5612	5892	6172	6452
total luminaire length											
inches	144	155	166	177	188	199	210	232	243	254	265
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

DESCRIPTION	CONTINUOUS RUNS										
	6732	7012	7292	7572	7852	8132	8412	8692	8972	9252	9532
total luminaire length											
inches	276	287	298	309	320	331	342	353	364	375	386
'560 board multiples	12.0	12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	16.5	17.0

CUSTOM LENGTHS

CUSTOM LENGTHS
Custom lengths for Proformax are available in 1.967" [50mm] increments above the minimum pendant length of 23" [585mm]

XTS | 2.0 Beam

Bend Options



135°



cross 90°



Tee 90°



custom



corner 90°




ceiling to wall

Optical Control (up)



plexiglass

Optical Control (down)



plexiglass



Accessories and options



sensors / daylight
harvesting



emergency packs



downlights

Rollerball Suspension

The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling or even a wall

Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.



Xero Linear Lighting Systems
14 Voyager Circuit, Glendenning NSW Australia 2761

General Enquiries
P: +61 2 8599 9788
E: headoffice@xerolighting.com

