

XTA | 3.0 Square IP55

metric	80mm Wide x 80mm High
imperial	3.149" Wide x 3.149" High



DATA TABLE

LED Engine	4ft Length 1120mm	Luminous Flux (Delivered Lumens)	LO 1900	HO 3500		
	Xeramix	CRI		80+		
Lumen Maintenance:		114,000 Hours (L90 B10 @ 50°C)				
Proformax		CRI:		90+		
		Lumen Maintenance:		82,000 Hours (L80 B10 @ 35°C)		
Warranty	Xeramix		10 years			
	Proformax		7 years			
Electrical	Power Consumption		Between 20 and 45w/m			
	Voltage input range		120 – 277V			
	Control methods		Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI			
	Total harmonic distortion THD		9.8% max			
	Approvals		UL / CE / CCC / AS:NZS / EMC			
Physical	Dimensions		80 X 80 mm			
	Weight per metre		3.3kg (7.3lbs) average weight			
	Distribution		Symmetric / Asymmetric			
	Housing		Aluminium Extrusion with anodised or powder-coated finish			
	Diffuser		Frosted acrylic lens / Polycarbonate lens / microprism lens			
	Connections		Speed connect joining system with polarised electrical connection between sections			
	Compatible ceiling type		Suitable for gyprock (drywall) ceilings, metal pan, concrete, timber and T-bar grid ceilings			
	Mounting		Field adjustable rollerball wire suspensions / rod suspensions / wall mounting / surface mount			
	Joiner options		Lit corner 90°/ Cross 90°/ Tee 90°/ straight 180° join			
	Operating temperatures		Xeramix = -25°C to 50°C (-13°F to 140°F) Proformax = -25°C to 35°C (-13°F to 95°F)			
	Environment		IP55 (Not in direct sunlight)			
	Minimum length adjustment		Xeramix = 1mm Proformax = 25mm			
	LED Board types		Xeramix LED boards in 25 / 100 / 280 / 560mm lengths Zhaga compatible Proformax LED boards in 50 / 280mm / 560mm lengths Zhaga compatible			

PENDANT LENGTHS

DESCRIPTION	PENDANT LENGTHS										
luminaire length	585	863.60	1143.00	1422.40	1701.80	1981.30	2260.60	2540.00	2819.40	3098.80	3378.20
inches	23	34	45	56	67	78	89	100	111	122	133
'560 board multiples	1	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0

CONTINUOUS LENGTHS

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	3657.60	3937.00	4216.40	4495.80	4775.20	5054.60	5334.00	5892.80	5892.80	6172.20	6451.60
inches	144	155	166	177	188	199	210	232	232	243	254
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

DESCRIPTION	CONTINUOUS RUNS										
total luminaire length	3657.60	3937.00	4216.40	4495.80	4775.20	5054.60	5334.00	5892.80	5892.80	6172.20	6451.60
inches	144	155	166	177	188	199	210	232	232	243	254
'560 board multiples	6.5	7	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5

CUSTOM LENGTHS

CUSTOM LENGTHS
custom lengths are available in 0.0393701" [1mm] increments above the minimum pendant length of 23" [585mm]


XTA | 3.0 Square IP55

Optical control


All XTA profiles come with many diffuser options for glare control in any application



Accessories and options




XM3 Canopy
Kit



sensors / daylight
harvesting



emergency packs



downlights

XTA | 3.0 Square IP55



The Xero Configurator allows you to design and build your customised lighting system. To ensure that your profile specifically caters to your project application follow the simple 8 step build process to obtain your unique DNA code. Select your profile, choose your colour, length, gear tray, output, colour temperature, mounting requirement and choose from the selection of extras

Project Specification Sheet

XTA 3.0 Beam

Name: Joe Smith
 Company: Joe Smiths Company
 Email: joesmith@joesmithcompany.com.au

Project: A very big project

Fitting Type:

Series	XTA - Advanced
IP Rating	IP55
LED Board	Xeramix X1
Size	3.0 Inches Down / 1.5 inches Up
Shape	Beam
Light Output	Up / Down
Diffuser	Plexiglass Down / Parabolic Louver Up
Colour Temp	3000K Down / 5000K Up
Drive Current	Drive Current Down / Drive Current Up
Total Light	Total Light Down / Total Light Up
Total Power	Total Power Down / Total Power Up
Efficiency	Efficiency Down / Total Power Up

[Copy and Paste into your project specification](#)

SPECIFICATION TEXT
[Copy and Paste into your project specification](#)

Type xx - XXM Xero XTA | 3.0 Square with Micro Prism diffuser, Xeramix I LED light engine, 3000°K, 50°C ambient temperature, L90 B10 14 hour life, 275Ma drive current. Efficacy of 512 lumens per watt delivered. Fitting comes complete with Speed-Connect joining system, Con Seal end plates and Lumiseal. Wire suspended with rollerball suspension system.

RE - CONFIGURE THIS SPECIFICATION
 This project specification sheet has been generated with X Configurator. Click below to reconfigure and generate a new specification sheet.

[Click to re-configure](#)

ADELAIDE | AUCKLAND | BRISBANE | CHRISTCHURCH | DUNEDIN | HONG KONG
 KUALA LUMPUR | SYDNEY | MELBOURNE | PERTH | USA | WELLINGTON

XEROLIGHTING.COM

to access the X-configurator please visit <https://xconfigurator.xerolighting.com/>

General enquiries
E headoffice@xerolighting.com W xerolighting.com
To get in touch with your local Xero
Distributor Visit [XEROContacts](#)



The information contained within this specification sheet is for general information purposes only. While Xero aspires to keep the information up to date and correct, we make no representations or warranties of any kind about the accuracy, reliability, suitability or availability with respect to this information, products, services, or graphics contained in this specification sheet for any purpose.