



XERO
Linear Lighting Systems

XERO
TECHNOLOGY
ADVANCED



XTA | 2.0 EDGE Recessed IP55

Size

2.16" Wide (inc flange 2.87"
Wide) 3.42" High



DATA TABLE

Output	CRI	80+
Warranty	Proformax	7 years
Electrical	Voltage input range	120 – 277V
	Control methods	Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI
	Total harmonic distortion THD	9.8% max
	Approvals	UL / CE / CCC / AS:NZS / EMC
Physical	Dimensions	2.16" Wide (including flange 2.87" Wide) x 3.42" High
	Weight	2.03 Lbs weight per foot
	Housing	Aluminium Extrusion with anodised or powder-coated finish Standard colours powder-coated: white/black/silver/ custom on request
	Diffuser	Polycarbonate Opal Diffuser/ Clear Polycarbonate Diffuser
	Connections	Speed connect joining system with polarised electrical connection between sections
	Compatible ceiling type	Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings
	Mounting	Drywall clips as standard
	Joiner options	Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join
	Operating temperatures	ProformaxS – (-13°F to 140°F)
	Environment	IP55 (Not in direct sunlight)
	Minimum length adjustment	5.51"
	LED Board types	ProformaxS boards in 5.51" / 11.02" / 22.0" lengths Zhaga compatible
	Optional Extras	Emergency packs


XTA | 2.0 EDGE Recessed IP55

Optical control

All XTA profiles come with many diffuser options for glare control in any application



Plexiglass



Microprism



Polycarbonate



Semi specular louvre




Optic white louvre

Accessories and options



sensors / daylight
harvesting



emergency packs



downlights

Bend options


XTA IP products are made with unlit corners.



135°




cross 90°



tee 90°



custom



corner 90°



ceiling to wall