

XERO
TECHNOLOGY
ADVANCED 

XTA | 3.0 Slot

Size

3.15" Wide x 4.52" High

DATA TABLE

| | | |
|-------------------|-------------------------------|---|
| Output | CRI | 80+ |
| Warranty | Proformax | 7 years |
| Electrical | Voltage input range | 120 – 277V |
| | Control methods | Dimming options for white light: 0-10V, DALI, DMX Optional RGB / Sunset Dimming control DMX or DALI XI |
| | Total harmonic distortion THD | 9.8% max |
| | Approvals | UL / CE / CCC / AS:NZS / EMC |
| Physical | Dimensions | 3.15" Wide x 4.52" High |
| | Weight | 2.56 Lbs weight per foot |
| | Housing | Aluminium Extrusion with anodised or powder-coated finish Standard colours powder-coated: white/black/silver/ custom on request |
| | Diffuser | Polycarbonate Opal Diffuser/ Clear Polycarbonate Diffuser / White Louvre / Semi Specular Louvre |
| | Connections | Speed connect joining system with polarised electrical connection between sections |
| | Compatible ceiling type | Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings |
| | Mounting | Surface Mounting / Custom Mounting / Rod Suspension / Wall Mounting |
| | Joiner options | Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join |
| | Operating temperatures | ProformaxS – (-13°F to 140°F) |
| | Environment | Dry indoor application only IP20 |
| | Minimum length adjustment | 5.51" |
| | LED Board types | ProformaxS boards in 5.51" / 11.02" / 22.0" lengths Zhaga compatible |
| Optional Extras | Emergency packs | |

XTA | 3.0 Slot
indoor series IP20

Optical control

All XTA profiles come with many diffuser options for glare control in any application



polycarbonate



plexiglass



microprism




optic white




semi specular
louvre


Accessories and options



sensors / daylight
harvesting



emergency packs



downlights

Bend options



135°



cross 90°



tee 90°



custom



corner 90°



ceiling to wall