

XERO  
TECHNOLOGY  
ADVANCED 

## XTA | 2.0 Slot

Size

2.36" Wide x 3.58" High



## DATA TABLE

<b>Output</b>	CRI	90+
<b>Warranty</b>	Proformax S	7 years
<b>Electrical</b>	Voltage input range	120 – 277V
	Control methods	Dimming options for white light: 0-10V
	Total harmonic distortion THD	<10%
	Approvals	UL / CE / CCC / AS:NZS / EMC
<b>Physical</b>	Dimensions	2.36" Wide x 3.58" High
	Weight	2.57 lbs average weight per foot
	Housing	Aluminium Extrusion with anodised or powder-coated finish Standard colours powder-coated: white/black/silver/ custom on request
	Diffuser	Plexiglass / Polycarbonate Opal Diffuser/ Clear Polycarbonate Diffuser / Optic White Louvre / Semi Specular Louvre / Low UGR Plexiglass
	Connections	Speed connect joining system with polarised electrical connection between sections
	Compatible ceiling type	Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings
	Mounting	Surface Mounting / Custom Mounting / Rod Suspension / Wall Mounting
	Joiner options	Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join
	Operating temperatures	ProformaxS – (-13°F to 95°F)
	Environment	Dry indoor application only IP20
	Minimum length adjustment	5.51"
	LED Board types	ProformaxS boards in 5.51" / 11.02" / 22.05" lengths Zhaga compatible
	Optional Extras	Emergency packs

# Optical control

All XTA profiles come with many diffuser options for glare control in any application



low UGR  
plexiglass



polycarbonate



plexiglass



microprism




optic white  
louvre



semi specular  
louvre

# Accessories and options



emergency packs