



XERO
Linear Lighting Systems

XTO
ADVANCED

XTA | 2.0 Beam

Size

2.36" Wide x 3.58" High



DATA TABLE

Output	CRI	90+
Warranty	Proformax S	7 years
Electrical	Voltage input range	120 – 277V
	Control methods	Dimming options for white light: 0-10V
	Total harmonic distortion THD	<10%
	Approvals	UL / CE / CCC / AS:NZS / EMC
Physical	Dimensions	2.36" Wide x 3.58" High
	Weight	4.47 lbs average weight per foot
	Housing	Aluminium extrusion with powder-coated finish: Standard powder-coated colours are: White / black and silver. Custom powder-coat on request
	Upward diffuser	Frosted acrylic lens / Polycarbonate lens / Microprism lens
	Downward diffuser	Frosted acrylic lens / Polycarbonate lens / Microprism lens / Semi specular louvre / White optic low brightness louvre / Low UGR Plexiglass
	Connections	Speed connect joining system with polarised electrical connection between sections
	Compatible ceiling type	Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings
	Mounting	Surface Mounting / Custom Mounting / Rod Suspension / Wall Mounting
	Joiner options	Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join
	Operating temperatures	ProformaxS – (-13°F to 95°F)
	Environment	Dry indoor application only IP20
	Minimum length adjustment	5.51"
	LED Board types	ProformaxS boards in 5.51" / 11.02" / 22.05" lengths Zhaga compatible
	Optional Extras	Emergency packs

Optical control (Down)

All XTA profiles come with many diffuser options for glare control in any application



low UGR
plexiglass



polycarbonate



plexiglass



microprism



optic white
louvre



semi specular
louvre

Optical control (Up)



polycarbonate



plexiglass



microprism

Accessories and options



emergency packs

XTA | 2.0 Beam

indoor series IP20

Highly Configurable

All XTA products can be made with lit, or unlit, corners which provide the designer with a myriad of design options.



bend options



135°



cross 90°



tee 90°



custom



corner 90°