



XERO
TECHNOLOGY
ADVANCED



XTA | 4.0 Square HO IP (High Output)

Semi outdoor only IP55

Size: 4.33" Wide x 4.33" High




LOW UGR
OPTION



Xero Linear Lighting Systems
General Enquiries
E: headoffice@xerolighting.com



XTA | 4.0 Square HO IP Dimensions



4.33"



4.33"

XTA | 4.0 Square HO IP55

DATA TABLE

Output	CRI	90+
Warranty	Proformax S	7 years
Electrical	Voltage input range	120 – 277V
	Control methods	Dimming options for white light: 0-10V
	Total harmonic distortion THD	<10% max
	Approvals	UL / CE / CCC / AS:NZS / EMC
Physical	Dimensions	4.33" Wide x 4.33" High
	Weight	3.41 Lbs average weight per foot
	Housing	Aluminium extrusion with powder-coated finish: Standard powder-coated colours are: White / black and silver. Custom powder-coat on request
	Diffuser	PlexiGlass
	Connections	Speed connect joining system with polarised electrical connection between sections
	Compatible ceiling type	Suitable for drywall ceilings, metal pan, concrete, timber and T bar grid ceilings
	Mounting	Surface Mounting / Custom Mounting / Rod Suspension / Wall Mounting
	Joiner options	Lit corner 90° / Cross 90° / Tee 90° / Straight 180° Join
	Operating temperatures	ProformaxS – (-13°F to 95°F)
	Environment	IP55 (Not in direct sunlight)
	Minimum length adjustment	5.51"
	LED Board types	ProformaxS boards in 5.51" / 11.02" / 22.05" lengths Zhaga compatible
	Optional Extras	Emergency packs

XTA | 4.0 Square HO IP55 Bend Options



135°



cross 90°



Tee 90°



custom



corner 90°

Optical Control



PlexiGlass



Accessories and options



emergency packs

Rollerball Suspension

The smart suspension system that can be mounted on any surface whether a flat or sloped ceiling or even a wall

Axis geartray

This truly unique innovation adopts our revolutionary cam lock for quick and simple 'single person' installation. The system is also 'future proofed' by having the ability to easily upgrade as LED technology rapidly advances.

